

Panel-Loc™

Wall and Roof Panel



The *classic panel* for post frame barns and buildings

The classic appearance of Panel-Loc gives agricultural and light commercial projects, as well as residential roofs, the protection of steel with an attractive appearance. Panel-Loc is engineered with CentralGuard® protection against fade, dent, and rust. Available in 26-gauge and 29-gauge metal panels, Panel-Loc is a reliable low-rib panel for metal buildings and roofs.

- Engineered with a Siphon Groove to minimize leaks.
- Customers may experience longer lead times as this panel is only produced in our Lowell, AR facility.



RECOMMENDED
3:12
PITCH
AND ABOVE

29 GAUGE
OR
26

36"
OVERALL
COVERAGE

5/8"
MAXIMUM
RIB HEIGHT

10274 W 600 South
Mentone, IN 46539
574-353-7701
Fax: 574-353-7183



NIFFTONE.COM

Copyright © 2021, Central States Manufacturing, Inc., All Rights Reserved.
CentralGuard® is a trademark of Central States® Manufacturing, Inc.
Galvalume® is a registered trademark of BIEC International, Inc.

FLYR_PL_200123.1

Choose CentralGuard[®] for the best protection and a lifetime warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Available on our Prime and Ultra panels, the CentralGuard name is a guarantee that you have the best protection and a lifetime paint warranty.

Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

	STANDARD	OUR BEST SELLER! PRIME CentralGuard	ULTRA CentralGuard
FADE PROTECTION			
Paint Warranty	40-YEAR	LIFETIME	LIFETIME
Paint Thickness	THICK .90 mil	THICKER 1.0 mil	THICKER 1.0 mil
Fade Warranty	30-YEAR	30-YEAR	30-YEAR
Fade Protection	✓	✓✓	✓✓
RUST BLOCKING			
Advanced Rust Blocking	–	✓	✓
Perforation Warranty	–	20-YEAR	20-YEAR
Substrate Thickness	1.12 mil	1.60 mil	1.60 mil
DENT RESISTANCE			
Advanced Dent Resistance	–	✓	✓✓
Steel Thickness	THIN	THICK	THICKEST
Steel Gauge	29 ga.	29 ga.	26 ga.

Panel-Loc features UL2218 approval for impact resistance and may qualify for a homeowners insurance discount. See your local insurance agent for qualifications.



MINIMUM SPECIFICATIONS FOR ULTRA AND PRIME PAINTED PANELS

GAUGE

Ultra 26 ga. | Prime 29 ga.

STEEL THICKNESS

Ultra 0.0185" | Prime 0.0150"

PAINT THICKNESS

Top coat paint: .70 mil
Top coat primer: .30 mil
Bottom coat backer: .35 mil
Bottom coat primer: .35 mil

TOTAL THICKNESS

Ultra 0.0202" | Prime 0.0167"

RUST PROTECTANT SUBSTRATE

Galvalume[®] AZ50

STEEL STRENGTH

80,000 PSI min

PAINT SYSTEM

SMP

WARRANTY

Lifetime limited paint adhesion
30-yr. chalk and fade
20-yr. Galvalume perforation

TESTING & APPROVALS

APPROVALS

UL2218 UL Approval, Impact Resistance, Class 4
UL790 UL Approval, Fire Resistance, Class A

Find more information at

NIFFTONE.COM